



 **ForceDry**
SCREED DRYING SPECIALISTS

TEL: 03301 244100

TEMPORARY
DEHUMIDIFIER HIRE



DEHUMIDIFIER SPECIFICATIONS



Maximum Operating Temp °C	35
Minimum Operating Temp °C	3
Typical Extraction (l/d)	30
Effective Volume (m3)	250
Noise Level (dba)	52
Airflow (m3/hr)	390
Current (A)	3 / 6
Power (kW)	680 watts
Frequency (Hz)	50
Phase	1
Voltage	110
Depth (mm)	492
Width (mm)	545
Height (mm)	945
Weight	48
On/Off Control Via Switch	Y
Electronic Humidstat	Y
Pump Purge Switch	Y
Hot Gas Defrost	Y
Electronic Defrost Timer	Y
Washable Filter	Y
Voltage Selection Switch	Y
Refrigerant Type	R407c
Free Standing	Y
Integral Condensate Pump	Y
Moulded Lifting Handles	Y
Ductable	Y
Cable Wrap	Y
Postable	Y



COMPANIES WE WORK WITH



MULTIPLEX



READ OUR CASE STUDIES [HERE](#).



CONTACT US TODAY

ForceDry
Unit 1 Sugarswell Business Park,
Shenington,
Banbury,
Oxfordshire.
OX15 6HW

Tel: 03301 244100

Email: info@force-dry.co.uk

Web: www.force-dry.co.uk

